



BICYCLE PARKING RACK DETAIL
NOT TO SCALE

NOTES:

1. UNLESS OTHERWISE APPROVED, BICYCLE PARKING RACKS SHALL BE "INVERTED U TYPE" CYCLE-SAFE U/2 BLACK PLASTISOL COATED BY MANUFACTURER OR APPROVED EQUIVALENT. OTHER RACKS MAY BE ALLOWED BUT MUST MEET THE FOLLOWING FUNCTIONAL REQUIREMENTS:
 - SUPPORT THE FRAME OF A BICYCLE IN TWO PLACES AND PREVENT THE BICYCLE FROM TIPPING OVER.
 - ALLOW THE FRAME AND ONE WHEEL TO BE LOCKED TO THE RACK WHEN BOTH WHEELS ARE LEFT ON THE BIKE.
 - ALLOW THE FRAME AND BOTH WHEELS TO BE LOCKED TO THE RACK IF THE FRONT WHEEL IS REMOVED.
 - ALLOW THE USE OF EITHER A CABLE OR U-SHAPED LOCK.
 - BE SECURELY ANCHORED BY SURFACE MOUNT.
 - BE USABLE BY BIKES WITH NO KICKSTAND.
 - BE USABLE BY BIKES WITH WATER BOTTLE CAGES.
 - BE USABLE BY A WIDE VARIETY OF SIZES AND TYPES OF BICYCLES.
 - BE COATED BY MANUFACTURER
2. INSTALL PER MANUFACTURER'S RECOMENDATION.

CITY OF KIRKLAND	
PLAN NO. CK-R.40	
	<p>BICYCLE PARKING RACK</p>