

Diagram illustrating the plan view of a trench and asphalt overlay. The diagram shows a cross-section of a road with a trench and an asphalt overlay. Key dimensions and labels include:

- 50'-0" MIN**: Minimum length of the trench.
- 5'-0" MIN**: Minimum width of the trench.
- 2'-0" MIN**: Minimum width of the asphalt overlay on either side of the trench.
- TRENCH**: Label pointing to the excavated area.
- ASPHALT OVERLAY FULL LANE WIDTH (TYP)**: Label pointing to the asphalt overlay area.
- CURB**: Label pointing to the curb area.
- PLAN VIEW**: Title of the diagram.
- NTS**: Not To Scale.

Diagram illustrating the cross-section of a pavement edge repair. The diagram shows a cross-section of a pavement edge with a 2" grind and overlay full lane width (typ). The repair is shown as a 2" thick overlay on a 2" thick grind. The edges of the pavement are labeled "EDGE OF PAVEMENT". The repair is labeled "2" GRIND AND OVERLAY FULL LANE WIDTH (TYP)". The edges of the repair are labeled "THOROUGHLY TACK ALL EDGES". A dashed line indicates the "TRENCH" location. A section line "A-A" is shown at the bottom, with "NTS" (Not To Scale) below it.

1. THIS STANDARD APPLIES TO ALL CUTS AND ARTERIAL STREETS AND ALL PAVEMENT LESS THAN 5 YEARS OLD.
2. OVERLAY AREA MAY BE MODIFIED BY CITY ON OLDER PAVEMENT DEPENDING ON CONDITIONS OR SCHEDULED CONSTRUCTION/MAINTENANCE.
3. ADJUST ALL UTILITY CASTING TO FINISH GRADE AND RESTORE CHANNELIZATION AND LOOP DETECTORS.
4. POTHOLES TO BE RESTORED WITH A 1' T-CUT. IF AFTER THE 1' T-CUT THE PATCH IS MORE THAN 4'x4', A GRIND AND OVERLAY IS REQUIRED UNLESS OTHERWISE APPROVED BY PUBLIC WORKS. IF THE PATCH IS WITHIN 2 LANES OF TRAVEL, THE GRIND AND OVERLAY WILL BE REQUIRED ON BOTH LANES. 50' MIN. LENGTH.
5. REFER TO COK STD. PLAN NO. CK-R.13C FOR REQUIREMENTS FOR GEOTECH BORING ASPHALT PATCHES.

The logo of the City of Kirkland, Washington, is a circular seal. It features a stylized illustration of a building with a prominent steeple, likely a church or a government building, situated on a small island or peninsula. A sailboat is depicted in the water to the right of the building. The words "CITY OF KIRKLAND" are written in a semi-circle at the top, and "WASHINGTON" is written in a semi-circle at the bottom.

ASPHALT OVERLAY FOR ROADWAY TRENCH REPAIR