


BILL OF MATERIALS

- (A) PRESSURE REGULATOR – WILKINS 600 SERIES OR EQUAL (WITH INTERNAL BYPASS AND STRAINER)
- (B) BRONZE GATE VALVE, 125-POUND, SOLID WEDGE OR DOUBLE DISC, WITH HANDWHEEL, OHIO BRASS, GRINNELL, OR EQUAL
- (C) NIPPLE x 2 1/2" LONG, MALE.
- (D) UNION, FEMALE.
- (E) ADAPTER, FEMALE x COMPRESSION FITTING FOR COPPER.
- (F) METER BOX FOR 1" INSTALLATION: FOGTITE B-10T IN NONTRAVELLED AREAS OR SIDEWALK. OLYMPIC FOUNDRY SM30 (18 3/4"x31"x16") IN AREAS WITH VEHICULAR TRAFFIC.
FOR 1 1/2" & 2" INSTALLATION:
17"x28" METER BOX W/TRAFFIC COVER AND 12" RISER, FOG TITE NO. 2T
- (G) 1" ROUND WASHED GRAVEL, 8" MIN. DEPTH.

NOTES:

1. PRESSURE REGULATOR SIZE AS SPECIFIED OR SHOWN ON PLAN.
2. SIZES FOR ITEMS (B) THROUGH (E) SHALL CORRESPOND TO THE SPECIFIED SIZE OF THE PRESSURE REGULATOR.
3. ALL FITTINGS AND NIPPLES ARE BRASS WITH IRON PIPE THREADS.

CITY OF KIRKLAND	
PLAN NO. CK- W.30	
 <p>CITY OF KIRKLAND WASHINGTON</p>	<p>INDIVIDUAL PRESSURE REDUCING VALVE ASSEMBLY—MULTI-FAMILY OR COMMERCIAL</p>