





6640 185th Ave NE, Redmond, WA 98052 T.425.895.8617, F.425.702.9358

CERTIFICATE #:

00243899

## CERTIFICATE OF CALIBRATION

## STANDARD CALIBRATION

## CLYDE HILL POLICE DEPARTMENT

9605 NE 24TH ST. CLYDE HILL. WA 98004

This certifies that the instrument listed herein was calibrated by Cascade Engineering Services' Calibration Laboratory, which is fully accredited in accordance with the recognized International Standards ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories. Cascade Engineering Services' Calibration Laboratory also meets the requirements of ANSI/NCSL Z540-1-1994 and any additional program requirements in the field of calibration. Standards used to perform this calibration are certified by or traceable to NIST, natural physical constants, consensus standards or derived by the ratio type of calibrations. All calibrations are performed to manufacturer's specifications unless otherwise noted. Standard Calibration, while still traceable, does not meet all requirements for an Accredited Calibration per ISO/IEC 17025:2017, that is "As Found" data for equipment in tolerance and Measurement Uncertainties are not recorded. This certificate shall not be reproduced, except in full, without prior written approval of the laboratory.

DESCRIPTION: SPE				EED MEASURING DEVICE			
ASSET #:	ET #: FH12675		SERIAL NUMBER:		FH12675		
MANUFACTURER: KL		KUSTOM	SIGNALS, INC.	MODEL NUMBER:			
DEPARTMENT:		N/A		PATROL CAR #:	N/A		
ENVIRONMENT:		68.0 °F/30.1 %RH		BASIC ACCURACY:	REFERENCE CAL PROCEDURE		CEDURE
CAL INTERVAL:		12 MONTHS		DUE DATE:	June 07, 2023		
EQUIPMENT CONDITION AS RECEIVED Initial testing found this equipment to be "IN TOLERANCE", as defined by the basic accuracy stated above.  EQUIPMENT CONDITION AS DELIVERED At the completion of the calibration, measured values were "IN TOLERANCE", as defined by the basic accuracy stated above.  TUNNING FORK(S) SUPPLIED WITH THIS DEVICE							
	DESCRIPTION		SERIAL NUMBER	RATED SPEED		FREQUEN	ICV
TUNING FO		33281	SERIAL NUMBER	A THE COLUMN TO SELECT THE SELECT THE COLUMN TO SEL	5 M.P.H.	FREQUEN	2540 Hz
	UNING FORK TWO 31332 65 M.P.H.						4692 Hz
Antenna 1 SN: HANDHELD, Frequency: 24.107 GHz							
STAND	ARD(S) US	ED FOR CE	RTIFICATION				
I.D.	MO	DEL	MANUFACTURER	DESCI	RIPTION		DUE DATE
MET1259	NOVA-DISPLA	Y O	PHIR	LASER POWER METER		TE MENT	03/09/2023
MET1260	PD300-SH	0	PHIR	LASER POWER HEAD			03/10/2023
PROCEDURE(S) USED FOR CERTIFICATION							
DOCUMENT ID				DESCRIPTION		REV	<b>REV DATE</b>
CP-SMD-00	)1	RADAR AND LIE	OAR CALIBRATION PROCE	DURE		NEW	11/14/2019
I certify (or declare) under penalty of perjury under the laws of the State of Washington that the above information is true and correct  LOCATION: Redmond, WA  PERFORMED BY CALIBRATION DATE: Tuesday, June 07, 2022							
THIS LABOR		REDITED TO ISO/IEC 1	7025:2017 (GENERAL REQUIREME	NTS FOR THE COMPETENCE OF TESTING AND	D CALIBRATION LABORA	TORIES), CERTIF	Page 1 of 1

MARCH 2020