

**NOTES:**

1. SEE CONTRACT PLANS AND SPECIFICATIONS FOR POLE HEIGHT, SIGN SHEETING TYPE, AND OTHER DETAILS. REFER TO PRE-APPROVED PLAN CK-R.43 FOR ADDITIONAL SIGN PLACEMENT REQUIREMENTS.
2. SEE CK-TS.12 AND CONTRACT SPECIAL PROVISIONS FOR APPROVED RRFB COMPONENTS. REFER TO PRE-APPROVED POLICY R-24 FOR POWER SOURCE DETERMINATION AND OTHER DETAILS.
3. THE PREFERRED PLACEMENT OF RRFB CONTROLLER CABINET IS BELOW THE W16-7P SIGN. IF THE RRFB IS LOCATED WITHIN OR ADJACENT TO A WALKING AREA, PROVIDE A MINIMUM 7' VERTICAL CLEARANCE TO BOTTOM OF CONTROLLER CABINET.
4. FOR SCHOOL CROSSINGS, AN S1-1 SIGN SHALL BE USED INSTEAD OF W11-2. IF USED, BOTH THE S1-1 AND W16-7P SHALL BE FLUORESCENT YELLOW GREEN IN COLOR.
5. THE RRFB POLE BASE AND FOUNDATION SHALL BE LOCATED SO THAT 4-FOOT MINIMUM CLEARANCE IS MAINTAINED FOR THE PEDESTRIAN ACCESS ROUTE. SIDEWALK WIDENING MAY BE REQUIRED TO ENSURE MINIMUM CLEARANCE DISTANCE.
6. ALL SIGNS SHALL HAVE ANTI-GRAFFITI COATING. SEE CONTRACT SPECIAL PROVISIONS FOR MORE INFORMATION.

	CITY OF KIRKLAND PLAN NO. CK - TS.14 RECTANGULAR RAPID FLASHING BEACON (RRFB) DETAIL	