

FILED

APR - 7 2022 KIRKLAND MUNICIPAL COURT



00242029

6640 185th Ave NE, Redmond, WA 98052 T.425.895.8617, F.425.702.9358

CERTIFICATE #:

# **CERTIFICATE OF CALIBRATION**

## STANDARD CALIBRATION

### CLYDE HILL POLICE DEPARTMENT

9605 NE 24TH ST. CLYDE HILL, WA 98004

This certifies that the instrument listed herein was calibrated by Cascade Engineering Services' Calibration Laboratory, which is fully accredited in accordance with the recognized International Standards ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories. Cascade Engineering Services' Calibration Laboratory also meets the requirements of ANSI/NCSL Z540-1-1994 and any additional program requirements in the field of calibration. Standards used to perform this calibration are certified by or traceable to NIST, natural physical constants, consensus standards or derived by the ratio type of calibrations. All calibrations are performed to manufacturer's specifications unless otherwise noted. Standard Calibration, while still traceable, does not meet all requirements for an Accredited Calibration per ISO/IEC 17025:2017, that is "As Found" data for equipment in tolerance and Measurement Uncertainties are not recorded. This certificate shall not be reproduced, except in full, without prior written approval of the laboratory.

#### DESCRIPTION: SPEED MEASURING DEVICE ASSET #: KK37897 SERIAL NUMBER: KK37897 MANUFACTURER: KUSTOM SIGNALS, INC. TROOPER MODEL NUMBER: DEPARTMENT: N/A PATROL CAR #: N/A 23.0 °C/32.4 %RH BASIC ACCURACY: REFERENCE CAL PROCEDURE ENVIRONMENT: CAL INTERVAL: **12 MONTHS** DUE DATE: April 07, 2023

#### EQUIPMENT CONDITION AS RECEIVED

Initial testing found this equipment to be "IN TOLERANCE", as defined by the basic accuracy stated above.

#### EQUIPMENT CONDITION AS DELIVERED

At the completion of the calibration, measured values were "IN TOLERANCE", as defined by the basic accuracy stated above.

#### TUNNING FORK(S) SUPPLIED WITH THIS DEVICE

DESCRIPTION		SERIAL NUMBER	RATED SPEED	FREQUENCY	
TUNING FORK ONE		3303	35 M.P.H.		2542 Hz
TUNING FORK TWO		3136	65 M.P.H.		4728 Hz
Antenna	1 SN: CC37517, Freq	uency: 24.142 GHz			
STAND.	ARD(S) USED FO	R CERTIFICATION			
I.D.	MODEL	MANUFACTURER	DESCRIPTION		DUE DATE
MET1231	VOCAR HR	DB INNOVATIONS	HAND HELD RADAR CERTIFICATION SYSTEM	Section Section	10/05/2022
MET1232	VOCAR HR WAND	DB INNOVATIONS	VOCAR HR WAND		10/05/2022
PROCE	DURE(S) USED F	OR CERTIFICATION			
DOCUMENT ID		DE	ESCRIPTION	REV	REV DATE
CP-SMD-001 RADAR AND LIDAR CALIBRATION PROCEDURE			URE	NEW	11/14/2019

#### CERTIFICATION NOTES

I certify (or declare) under penalty of perjury under the laws of the State of Washington that the above information is true and correct

PERFORMED BY

LOCATION: Redmond, WA CALIBRATION DATE: Thursday, April 07, 2022

THIS LABORATORY IS A2LA ACCREDITED TO ISO/IEC 17025:2017 (GENERAL REQUIREMENTS FOR THE COMPETENCE OF TESTING AND CALIBRATION LABORATORIES). CERTIFICATE #: 2560.01
F540-1.3/REVISION M
MARCH 2020
Page 1 of 1
MARCH 2020

THIS DOCUMENT IS MAINTAINED AS A PUBLIC RECORD IN ACCORDANCE WITH RCW 5.44